



## INVERTER Split type

### STYLISH DESIGN



Zen White (W)



Zen Silver (S)



Zen Black (B)

ความเย็นสบายบวกความเรียบง่ายในสไตล์ Zen  
ผ่านดีไซน์ที่หรูหรา สง่างาม กับสีที่เป็นเอกลักษณ์  
สะท้อนช่วงเวลาและอารมณ์อันแสนสงบและสบาย

#### MSZ-EF09VA (W/S/B)

8,530.00 BTU

SEER 19.22



ห้องขนาด 9-14 ตร.ม.\*

Capacity 2.5kW

#### MSZ-EF13VA (W/S/B)

11,942.00 BTU

SEER 16.32



ห้องขนาด 14-18 ตร.ม.\*

Capacity 3.5kW





MODEL		MOVE-EYE HUMAN SENSOR			KIRIGAMINE ZEN		SUPER INVERTER						
		MSZ-FK09VA	MSZ-FK13VA	MSZ-FK18VA	MSZ-EF09VA	MSZ-EF13VA	MSY-GK09VA	MSY-GK13VA	MSY-GK15VA	MSY-GK18VA	MSY-GK24VA		
Cooling	EGAT Level 5												
	SEASONAL ENERGY EFFICIENCY RATIO (SEER)	(Btu/h/W)	21.10	16.65	18.26	19.22	16.32	17.12	15.49	15.34	15.41	15.80	
	Capacity Rated (Min-Max)	Btu/h	8,871.20 (4,780 - 11,940)	12,965.60 (4,780 - 13,650)	17,401.00 (6,482 - 20,472)	8,530.00 (4,094 - 11,601)	11,942.00 (4,777 - 13,648)	8,530.00 (3,753 - 10,918)	11,942.00 (4,777 - 13,307)	14,330.40 (3,071 - 16,378)	17,401.20 (5,118 - 20,472)	22,519.20 (8,189 - 26,614)	
		kW	2.6 (1.4 - 3.5)	3.8 (1.4 - 4.0)	5.1 (1.9 - 6.0)	2.5 (1.2 - 3.4)	3.5 (1.4 - 4.0)	2.5 (1.1 - 3.2)	3.5 (1.4 - 3.9)	4.2 (0.9 - 4.8)	5.1 (1.5 - 6.0)	6.6 (2.4 - 7.8)	
	Total Input (Min-Rated-Max)	kW	0.21 - 0.54 - 0.98	0.21 - 1.00 - 1.28	0.41 - 1.44 - 2.25	0.24 - 0.57 - 1.15	0.21 - 0.94 - 1.50	0.20 - 0.64 - 1.04	0.32 - 0.99 - 1.56	0.16 - 1.20 - 1.94	0.32 - 1.45 - 2.10	0.57 - 1.83 - 3.00	
	Running Current	A	2.8	4.8	6.8	3.0	4.5	3.3	4.7	5.6	6.7	8.4	
	SPL Indoor	Silent	dB(A)	20	21	29	21		19	20	26	28	30
		Low		23	24	31	23		21	23	30	33	36
		High		36		39	36		36	38	40	44	46
Air Circulation (Low - High)	m <sup>3</sup> /min	4.7 - 8.6		6.4 - 10.1	4.6 - 8.3		4.8 - 8.8	5.6 - 10.2	6.1 - 9.7	11.2 - 15.6	11.9 - 16.8		
Heating	Capacity Rated (Min-Max)	kW	3.2 (1.7 - 4.2)	4.0 (1.7 - 5.3)	6.0 (1.7 - 8.7)	3.2 (1.1 - 4.2)	4.0 (1.8 - 5.5)	-					
	Total Input (Min-Rated-Max)	kW	0.27 - 0.64 - 1.47	0.27 - 0.89 - 1.47	0.43 - 1.53 - 3.06	0.25 - 0.73 - 1.17	0.28 - 0.97 - 1.53	-					
	Running Current	A	3.2	4.3	7.2	3.7	4.6	-					
	SPL Indoor	Silent	dB(A)	20	21	25	21		-				
		Low		24		29	24		-				
		High		36		39	37	38	-				
Air Circulation (Low-High)	m <sup>3</sup> /min	4.7 - 9.2		5.7 - 11.2	4.6 - 8.9		-						
Coefficient of performance (Rated Cooling / Heating)	(W/W)	4.81 / 5.0	3.80 / 4.49	3.92	4.39 / 4.38	3.72 / 4.12	3.91 / -	3.54 / -	3.50 / -	3.52 / -	3.61 / -		
Power supply		220 V / Single phase / 50 Hz			220V / Single phase / 50 Hz		220 V / Single phase / 50 Hz						
Operating Current Max	A	10		14	7.3	8.5	6.5		8.9	9.1	14.6		
Features	Microprocessor control		O			O		O					
	Automatic temperature control		O			O		O					
	Timer switch		Weekly timer			Weekly timer		24 Hr. ON/OFF program timer		Weekly timer			
	Remote control switch		Wireless			Wireless		Wireless					
	Indoor fan speeds		5+AUTO			5+AUTO		5+AUTO					
	Blow fan	Indoor	Line flow fan			Line flow fan		Line flow fan					
Outdoor		Propeller			Propeller		Propeller						
Dimensions (H x W x D)	Indoor unit	mm	305 (+17) x 925 x 234			299 x 895 x 195		295 x 798 x 232		325 x 1100 x 238			
	Outdoor unit	mm	550 x 800 x 285		880x 840 x330	550 x 800 x 285		550 x 800 x 285			880 x 840 x 330		
Weight	Indoor unit	kg	13.5			11.5		10		16			
	Outdoor unit	kg	35	55	30	35	29	35		50			
Piping size (Outer Diameter)	Liquid	mm.in	6.35 (1/4)			6.35 (1/4)		6.35 (1/4)					
	Gas	mm.in	9.52 (3/8)		12.7(1/2)	9.52(3/8)		9.52 (3/8)		12.7 (1/2)	15.88 (5/8)		
	Max.Length / Max.Height	m	20 / 12		30/15	20 / 12		20 / 12			30 / 15 (5/8)		
Refrigerant		R410A											



พ.ศ. 1155-2536

พ.ศ. 2134-2553

ผลิตภัณฑ์โรงงานที่ได้มาตรฐาน ISO9001 และ ISO14001

รับประกันแผงคอยล์ขึ้น 3 ปี

รับประกันคอมเพรสเซอร์ 5 ปี

ปลอดภัยเหนือสิ่งอื่นใด