



## E4 SERIES-KD



### Super Cooling

With the QSD technology, the compressor can start in just one second, just like a sport car, so you won't have to wait for the cooling!



### Self-cleaning

Via a frosting, penetration, stripping, defrosting and drying cycle, can easily regain a clean AC. Improve the efficiency of heat exchange to ensure the AC in better cooling.



### I Feel

Because the sensor on the remote control can detect its surrounding temperature. When you press the "I Feel" button, the indoor temperature is very stable and accurate, body will feel very comfortable.

## E4 Series-KD



| Customer Model No.        | AS-10TR4D3T       | AS-12TR4D3T       | AS-18TR4D3T        | AS-22TR4D3T       |
|---------------------------|-------------------|-------------------|--------------------|-------------------|
| Factory Model No.         | AS-10TR4D3T       | AS-12TR4D3T       | AS-18TR4D3T        | AS-22TR4D3T       |
| Type                      | TL CO. Inverter   | TL CO. Inverter   | TL CO. Inverter    | TL CO. Inverter   |
| Cooling Capacity          | Btu/h             | 9500              | 12000              | 18000             |
| Cooling Capacity          | W                 | 9500 (2860-10900) | 12000 (2860-12960) | 18000 (3150-3900) |
| Rated Input - Cooling     | W                 | 770               | 1130               | 1680              |
| Air Circulation (Indoor)  | m <sup>3</sup> /h | 580               | 580                | 950               |
| SEER                      | Btu/W.h           | 17.20             | 17.81              | 18.02             |
| Energy Class              | Cooling           | A++               | A++                | A++               |
| Refrigerant               | R32               | R32               | R32                | R32               |
| Refrigerant Charge Volume | g                 | 450               | 520                | 880               |
| Indoor Sound Pressure     | dB (A)            | 38/34/29          | 38/34/29           | 45                |
| Outdoor Sound Pressure    | dB (A)            | 51                | 51                 | 54                |
| Voltage, Frequency        | V                 | 220-240V, 50Hz/3P | 220-240V, 50Hz/3P  | 220-240V, 50Hz/3P |
| Rated Current             | Cooling (A)       | 3.4               | 5.0                | 7.0               |
| Maximal Pipe Length       | m                 | 20                | 20                 | 25                |
| Maximal Height Interval   | m                 | 10                | 10                 | 10                |
| Liquid Pipe               | inch              | 1/4               | 1/4                | 3/8               |
| Gas Pipe                  | inch              | 3/8               | 3/8                | 1/2               |
| Net Dimensions            | Indoor Unit       | 790x255x200       | 790x255x200        | 840x310x220       |
| Net Dimensions            | Outdoor Unit      | 660x482x240       | 870x283x468        | 780x290x340       |
| Net Weight (kg)           | Indoor Unit       | 7.3               | 7.5                | 10.0              |
| Net Weight (kg)           | Outdoor Unit      | 19                | 20.5               | 28.0              |