



STERILIZATION SERIES-LB



Cold Plasma
Generator



Self-cleaning



I Feel



Inverter



HEPA&4-In-1
Filter



4D
auto wing



fast
cooling



100%
copper pipes



Golden fin

Customer	Model No.	AS10TRLB2T	AS13TRLB2T	AS18TRLB2T	AS24TRLB2T
Factory	Model No	AS-10TR4RYETU00	AS-12TR4RYETU00	AS-18TR4RMATD02	AS-22TR4RXBTD01
Type		T1,CO, Inverter	T1,CO, Inverter	T1,CO, Inverter	T1,CO, Inverter
Cooling Capacity	Btu/h	9500(2860 -10900)	12000(2860 -12960)	18300(4100 -18800)	22860(4100 -24900)
Cooling Capacity	W	2800	3500	5300	6700
Rated Input-Cooling	W	750	1080	1500	1870
Air Circulation (Indoor)	m³/h	600	600	1000	1100
SEER	Btu/W.h	18.60	20.00	19.14	19.31
Energy Class	Cooling	No.5 ★	No.5 ★★	No.5 ★	No.5 ★
Refrigerant		R32	R32	R32	R32
Refrigerant charge volume	g	430	600	920	1150
indoor Sound Pressure(L/M/H)	dB (A)	37/33/28	37/33/28	46/42/37	46/42/37
outdoor Sound pressure	dB (A)	49	49	56	54
Voltage, Frequency, Phase	V	220-240V~,50Hz,1P	220-240V~,50Hz,1P	220-240V~,50Hz,1P	220-240V~,50Hz,1P
Rated Current	Cooling (A)	3.4	4.4	6.7	8.4
maximal pipe length	m	20	20	25	25
maximal heights' interval	m	10	10	10	10
Liquid Pipe	inch	1/4	1/4	1/4	3/8
Gas Pipe	inch	3/8	3/8	1/2	5/8
Net Dimensions WxHxD (mm)	Indoor Unit	866× 270× 213	866× 270× 213	908× 315× 230	1121× 314× 263
	Outdoor Unit	660× 482× 240	660× 482× 240	780× 260× 540	810× 129× 562
Net Weight (Kg)	Indoor Unit	7.0	7.3	12.0	14
	Outdoor Unit	21.5	22.5	27.0	33.5